

BYK-390

Version 6

Revision Date 08/05/2013

Print Date 09/13/2013

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : BYK-390
 Product Use Description : Leveling Additive

 Company : BYK USA Inc.
 524 South Cherry Street
 Wallingford CT 06492

 Prepared by : J.Nole, Safety; M.McCutcheon, Regulatory
 Telephone : (203) 265-2086
 Visit our web site : www.byk.com
 E-mail address : ehs.byk.usa@altana.com
 Emergency telephone number : CHEMTREC 1-800-424-9300 / +1 703-527-3887

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : liquid
 Colour : light yellow
 Odour : solvent-like

OSHA Regulatory Status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR1910.1200)

Potential Health Effects

Eyes : Contact will probably cause irritation.
 Skin : Contact will probably cause irritation.
 Ingestion : May irritate the digestive tract and cause same symptoms as inhalation; high dosages may result in unconsciousness.
 Inhalation : High concentrations of vapors may be irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness, loss of coordination and fatigue).
 Chronic Exposure : Absorption of ingredients (solvents) by inhalation and/or repeated skin contact has caused injury to liver, kidney, brain, respiratory system, blood, and/or bone marrow in laboratory animals
 Animal studies have shown ingredients caused fetotoxic effects at or near maternally toxic levels. Excessive inhalation of Xylene has caused hearing loss in laboratory animals. Hexane used in conjunction w/Xylene increased this effect. Chronic skin contact w/Xylene has caused dermatitis.

Material Safety Data Sheet



BYK-390

Version 6

Revision Date 08/05/2013

Print Date 09/13/2013

Ingestion of Ethanol can increase the effects of over-exposure to Xylene.

Ethylbenzene is an IARC Group 2B carcinogen based on animal studies (increased tumors in rats and mice).

Aggravated Medical Condition : May be aggravating to some skin conditions
asthma-type conditions
pre-existing liver and/or kidney disorders

Primary Routes of Entry : Skin contact
Skin absorption
Inhalation
Eyes
Ingestion

Carcinogenicity:

IARC	Ethylbenzene	100-41-4
------	--------------	----------

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

ACGIH	Ethylbenzene	100-41-4
-------	--------------	----------

Environmental Effects

Environmental Effects : No information available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

Solution of a polyacrylate

Hazardous components

Ethylbenzene is a component of Xylene.

Component	CAS-No.	Weight percent
Xylene	1330-20-7	30.00 - 60.00
Ethylbenzene	100-41-4	10.00 - 30.00

BYK-390

Version 6

Revision Date 08/05/2013

Print Date 09/13/2013

SECTION 4. FIRST AID MEASURES**First aid procedures**

- Inhalation : Remove to fresh air. Administer artificial respiration if necessary. Get medical aid as soon as possible.
- Skin contact : Remove contaminated clothing. Wash thoroughly with soap and water.
- Eye contact : Immediately flush with plenty of water for at least 20 minutes. Get medical aid.
- Ingestion : Do not induce vomiting; aspiration hazard. Dilute with 1-2 glasses of water. Get medical aid. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.

Notes to physician

- Risks : No information available.

SECTION 5. FIREFIGHTING MEASURES**Flammable properties**

- Flash point : 27 °C (80.60 °F)
Method: 48 (Abel-Pensky)
- Ignition temperature : > 300 °C (> 572.00 °F)
Method: calculated
- Lower explosion limit : 1.00 %(V)
- Upper explosion limit : 7.50 %(V)
- Suitable extinguishing media : Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : No information available.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Specific hazards during firefighting : Cool closed containers exposed to fire with water spray.
Will not explode on mechanical impact.
- Hazardous decomposition : Carbon oxides

BYK-390

Version 6

Revision Date 08/05/2013

Print Date 09/13/2013

products due to incomplete combustion. nitrogen oxides (NOx)
 Further information : Keep away from heat and sources of ignition.
 Keep away from oxidizing agents.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Eliminate all sources of ignition. Ventilate area if indoors. Wear self-contained breathing apparatus and full protective clothing.
 Environmental precautions : Prevent spilled material from entering the ground, water and/or air by using appropriate containment methods.
 Methods for containment : Stop leak. Dike and contain spill.
 Methods for cleaning up : Pump into salvage tanks and/or absorb with suitable material. Use sparkless shovels to remove material.
 Additional advice : No further information is available.

SECTION 7. HANDLING AND STORAGE

Handling

Handling : Harmful in contact with skin.
 Avoid contact with skin and eyes.
 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 Handle as an industrial chemical.
 Keep container tightly closed.
 Keep away from oxidizing agents.

Storage

Advice on common storage : Keep product and empty container away from heat and sources of ignition.
 Take precautionary measures against static discharges.
 Keep in a dry, cool and well-ventilated place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
Xylene	1330-20-7	TWA	100 ppm	2007-01-01	ACGIH

BYK-390

Version 6

Revision Date 08/05/2013

Print Date 09/13/2013

		STEL	150 ppm	2007-01-01	ACGIH
		TWA	100 ppm 435 mg/m3	1997-08-04	OSHA Z-1
		TWA	100 ppm 435 mg/m3	1989-01-19	OSHA P0
		STEL	150 ppm 655 mg/m3	1989-01-19	OSHA P0
Ethylbenzene	100-41-4	TWA	100 ppm	2009-01-01	ACGIH
		TWA	20 ppm	2012-01-01	ACGIH
		TWA	100 ppm 435 mg/m3	1997-08-04	OSHA Z-1
		TWA	100 ppm 435 mg/m3	1989-01-19	OSHA P0
		STEL	125 ppm 545 mg/m3	1989-01-19	OSHA P0

Engineering measures

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Eye protection : Safety Glasses
Goggles

Hand protection : Nitrile rubber

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Unless air monitoring demonstrates vapor/mist/dust levels are

BYK-390

Version 6

Revision Date 08/05/2013

Print Date 09/13/2013

below the PEL/TLV wear a properly fitted respirator (NIOSH approved) or dust mask during exposure.

Hygiene measures : Clean long legged, long sleeved work clothes.
Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: liquid
Colour	: light yellow
Odour	: solvent-like
Odor Threshold	: no data available
Flash point	: 27 °C (80.60 °F) Method: 48 (Abel-Pensky)
Ignition temperature	: > 300 °C (> 572.00 °F) Method: calculated
Lower explosion limit	: 1.00 %(V)
Upper explosion limit	: 7.50 %(V)
pH	: no data available
Freezing point	: no data available
Initial boiling point	: 137 °C (278.60 °F)
Vapour pressure	: 8.0000000 hPa at 20 °C (68.00 °F) Method: calculated
Evaporation rate	: no data available
Density	: 0.9000 g/cm ³ at 20 °C (68.00 °F)Method: DIN EN ISO 2811-3
Bulk density	: not applicable
Water solubility	: immiscible
Partition coefficient: n-octanol/water	: no data available
Viscosity, kinematic	: at 20 °C (68.00 °F) no data available 220 mm ² /s at 40 °C (104.00 °F)
Relative vapour density	: no data available

BYK-390

Version 6

Revision Date 08/05/2013

Print Date 09/13/2013

SECTION 10. STABILITY AND REACTIVITY

- Conditions to avoid : None known.
- Materials to avoid : Strong oxidizing agents
- Hazardous decomposition products : None expected
- Chemical stability : Stable; polymerization will not occur

SECTION 11. TOXICOLOGICAL INFORMATION

- Acute oral toxicity (Product) : LD50 rat
Dose: > 4,000.000000 mg/kg
Method: OECD Test Guideline 401
active ingredient
- Acute oral toxicity (Component) : Component: 1330-20-7 Xylene
LD50 rat
Dose: 3,523 mg/kg
- Component: 100-41-4 Ethylbenzene
LD50 rat
Dose: 3,500 mg/kg
- Acute dermal toxicity (Component) : Component: 1330-20-7 Xylene
LD50 rabbit
Dose: 1,700 mg/kg
- Component: 100-41-4 Ethylbenzene
LD50 rabbit
Dose: 5,510 mg/kg
- Acute inhalation toxicity (Component) : Component: 1330-20-7 Xylene
LC50 rat
Dose: 5000 ppm
Exposure time: 4 h
- Component: 100-41-4 Ethylbenzene
LC50
no data available
- Skin irritation (Product) : rabbit
Result: Mild skin irritation
Method: OECD Test Guideline 404
active ingredient

Material Safety Data Sheet



BYK-390

Version 6

Revision Date 08/05/2013

Print Date 09/13/2013

Skin irritation (Component) : Component: 1330-20-7 Xylene
rabbit
Result: Moderate skin irritation

Component: 100-41-4 Ethylbenzene
rabbit
Result: Moderate skin irritation

Eye irritation (Product) : rabbit
Result: Mild eye irritation
Method: OECD Test Guideline 405
active ingredient

Eye irritation(Component) : Component: 1330-20-7 Xylene
rabbit
Result: Eye irritation

Component: 100-41-4 Ethylbenzene
rabbit
Result: Moderate eye irritation

Sensitisation (Product) : no data available

SECTION 12. ECOLOGICAL INFORMATION

Additional ecological information (Product) : There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Further information : Dispose of in accordance with applicable local/municipal, state/provincial and federal regulations.

SECTION 14. TRANSPORT INFORMATION

Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples)
CERCLA RQ: Drums Only (Xylene 100 pounds)

DOT UN Number : 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Xylene, Ethylbenzene)
Class : 3
Packing group : III
Emergency Response : 128
Guidebook Number

Material Safety Data Sheet



BYK-390

Version 6

Revision Date 08/05/2013

Print Date 09/13/2013

IATA UN Number : 1993
Description of the goods : FLAMMABLE LIQUID, N.O.S.
(Xylene, Ethylbenzene)
Class : 3
Packing group : III
ICAO-Labels : 3
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355
Package Instruction (Limited quantity) : Y344

IMDG UN Number : UN 1993
Description of the goods : FLAMMABLE LIQUID, N.O.S.
IMDG Code segregation group - none
(Xylene, Ethylbenzene)
Class : 3
Packing group : III
IMDG-Labels : 3
EmSNumber1 : F-E
EmSNumber2 : S-E
Marine pollutant : no
IMDG Code segregation group - none

SECTION 15. REGULATORY INFORMATION

HMIS Classification : Health hazard: 2
Chronic Health Hazard: *
Flammability: 3
Reactivity: 0
PPI:B

National Fire Protection Association (NFPA) Class : IC

Emergency Planning Community Right-To-Know (EPCRA)

SARA 302 Components : Not applicable

If listed below, this product contains toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

SARA 313 Components	:	Xylene	1330-20-7	38.3%
		Ethylbenzene	100-41-4	9.5%

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard
Fire Hazard

BYK-390

Version 6

Revision Date 08/05/2013

Print Date 09/13/2013

Toxic Substances Control Act (TSCA)

TSCA Status : We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).

Section 4 / 12(b) : Not applicable

Clean Air Act & Related Information

Non-volatile (Wt) : 47 - 53 %
 Method: 51 (60min/105°C/ 1g)
 DIN EN ISO 3251

Ozone Depleting Substances : Not applicable.

Non-volatile information is not a specification.

Hazardous Air Pollutants

Xylene	1330-20-7
Ethylbenzene	100-41-4

If not listed above, this product does not contain HAPs at 1% or 0.1% or greater. Refer to Section 3 for HAP weight percentage.

Resource Conservation and Recovery Act

EPA Hazardous Waste Code(s)	: D001	Ignitable
	D018	Benzene

State Laws

Massachusetts Right To Know Components	: Xylene	1330-20-7
	Ethylbenzene	100-41-4

Pennsylvania Right To Know Components	: Xylene	1330-20-7
	Ethylbenzene	100-41-4

New Jersey Right To Know Components	: Xylene	1330-20-7
	Ethylbenzene	100-41-4

Material Safety Data Sheet



BYK-390

Version 6

Revision Date 08/05/2013

Print Date 09/13/2013

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : 800963-5105

California Prop. 65 Components : WARNING! This product contains a chemical known to the State of California to cause cancer.

Ethylbenzene 100-41-4
Benzene 71-43-2

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Toluene 108-88-3
Benzene 71-43-2

Does not contain heavy metals (according to formulation).
CONEG Heavy Metal: We certify that this product does not contain Lead, Mercury, Cadmium or hexavalent chromium in the sum concentration of 100 ppm by weight or greater.

Canadian Environmental Protection Act

Domestic Substances List

DSL Status : We certify that all of the components of this product are listed on the DSL.

WHMIS Classification : B2
D2A
D2B

SECTION 16. OTHER INFORMATION

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Material Safety Data Sheet



BYK-390

Version 6

Revision Date 08/05/2013

Print Date 09/13/2013

Identification, Hazard, Precaution, and other safety information sections, including a table of physical and chemical properties.

Additional information, handling instructions, and contact details for BYK Additives & Instruments.