

SECTION I - PRODUCT IDENTIFICATION

Trade Name: **GS-43MR**
Product Class: Butyl Base Sealant
Supplier: **Airtech International, Inc.**
5700 Skylab Road
Huntington Beach, CA 92647
Telephone: 714-899-8100
Fax: 714-899-8179

Emergency Telephone: **800-424-9300**

CERCLA Ratings: Health= Fire= Reactivity= Persistence=
(scale 0-3)
NFPA Ratings: Health= 0 Fire= 0 Reactivity= 0
(scale 0-4)

SECTION II – HAZARDOUS INGREDIENTS

This material is not considered to be hazardous according to regulatory guidelines.

SECTION III – FIRST AID MEASURES

Eye contact: Flush with warm water for 15 minutes. If irritation persists, seek medical attention.
Skin contact: Wash contaminated area with soap and water for 15 minutes. If irritation persists, seek medical attention.
Ingestion: Do not induce vomiting. Seek medical attention.
Inhalation: Remove to fresh air. Seek medical attention.

SECTION IV – FIRE FIGHTING MEASURES

Flash point: N/A
Auto ignition point: N/A
Lower explosive limit: N/A
Upper explosive limit: N/A

Extinguishing media: Use water spray (fog), foam, dry chemical or carbon dioxide (CO2).

Fire fighting instructions: Use water spray to cool fire exposed surfaces. Use standard protective equipment and in enclosed spaces a self contained breathing apparatus.
Fire and explosion hazards: Irritating gases may be present.

SECTION V – ACCIDENTAL RELEASE MEASURES

Avoid release to the environment. Contain spill, collect, and transfer to suitable containers. Do not flush to sewer or allow to enter waterways. Recycle or dispose in accordance with federal, state, and local regulations.

SECTION VI – HANDLING AND STORAGE

Store in closed containers at 72° F. Avoid excessive heat. For industrial use only.

SECTION VII – EXPOSURE CONTROLS/ PERSONAL PROTECTION

Engineering controls: Use with adequate general ventilation.
Eye/face protection: N/A
Skin protection: Use gloves when material is hot.
Respiratory protection: N/A
Other/General protection: Wash thoroughly after handling.

SECTION VIII – PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White
Odor: No odor
Chemical type: Mixture
Physical state: Solid
Melting point: N/A
Boiling point: N/A
Specific gravity (Water = 1): 1.29
Vapor pressure: N/A
Vapor Density (Air=1): N/A
Solubility in water: Insoluble
Evaporation rate (n-butyl Acetate=1): N/A

SECTION IX – STABILITY AND REACTIVITY

Stability: Stable

Hazardous polymerization: Will not occur

Incompatible Materials: Strong oxidizing agents

Hazardous decomposition products: Thermal decomposition may form carbon dioxide, carbon monoxide and various hydrocarbon fumes.

Condition to avoid: None known.

USER'S RESPONSIBILITY

This bulletin cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. It is your responsibility to use this information to develop appropriate work practice guidelines and employee instructional programs for your operation.

DISCLAIMER OF LIABILITY

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state and local laws and regulations remains the responsibility of the user.

Data Sheet

GS-43MR

High tack and high temperature sealant tape

DESCRIPTION

GS 43MR is the most reliable sealant tape with excellent tack and clean-up. It is usable up to 450 °F (232 °C).

TECHNICAL DATA

Color Off-white
Base material Synthetic rubber
Maximum use temperature 450 °F (232 °C)
Shelf life 12 months from date of manufacture
Storage conditions 72 °F (22 °C)
Do not refrigerate
Tape must be stored flat in original carton.

SIZES

Dimensions	Packaging	Remarks
1/8 inch x 1/2 inch x 25 feet (3 mm x 12 mm x 7.5m)	40 rolls per case	-
1/8 inch x 3/4 inch x 25 feet (3 mm x 19 mm x 7.5 m)	28 rolls per case	-

NOTES

For clean removal, it is recommended to strip the tape from the mold surface once it has cooled down to room temperature.

Catalog position : Vacuum bag sealant tapes

Last updated : 2013-12-17