



MATERIAL SAFETY DATA SHEET

NOTE: BLANK SPACES ARE NOT P	ERMITT	ED. IF ANY ITE	M IS NOT APPLICABLE,	THE SPACE MUST	T BE MARKED	TO INDICATE THAT.	
IDENTITY			PART NO.				
(As shown on Label or package) PLA	nd PLASTI DIP	UV (F-698, 819, 820)	IF APPLICAB	LE			
SECTION I							
MANUFACTURER'S EMERGENCY PHONE No.							
NAME Plasti Dip Internati	onal Inc			USA only: 1-80	USA only: 1-800-424-9300 INT'L: 703-527-3887		
ADDRESS (NUMBER, STREET, CITY)	REVISION#					
3920 Pheasant Ridge Drive		······································		MANUFACTURER'S PHONE			
Blaine, MN 55449	No. FOR INFORMATION 1-763-785-2156						
Diame, Will Johns	DATE MSDS						
	WAS PREPARED October 17, 2008						
SECTION II - HAZARDOUS INGRED	TENTS IN	FORMATION.	All Health Hazards which c				
carcinogens if 0.1% of the composition	or greater	. Januarioin					
HAZARDOUS COMPONENTS CHEM		% Wt.	CAS NO.	OSHA	ACGIH	OTHER LIMITS	
and IDENTITY AND COMMON NAM	ME (S)	(OPTIONAL)		PEL	TLV	RECOMMEND	
VM&P Naphtha	- \-''	32 – 38	64742-89-8	300 ppm	300 ppm	None	
Hexane		16-19	110-54-3	500 ppm	50 ppm	None	
Toluene		13-16	108-88-3	200 ppm	50 ppm	None	
Methyl Ethyl Ketone		3-7	78-93-3	200 ppm	200 ppm	None	
Resins		25-27	N/A	N/A	N/A	None	
SECTION III - PHYSICAL / CHEMIC	AL CHA	1.00			_		
BOILING		IC GRAVITY (H ₂ 0 =1)		APPROXIMA	APPROXIMATE WEIGHT PER GALLON (LBS)		
POINT 149-285°F	SIECIE.		9 – 0.83				
VAPOR PRESSURE	VAPOR DENSITY			EVAPORATION RATE			
125 mmHg @ 20°C		 Heavier than air 	r		(BUTYL ACETATE =1) >1.0		
SOLUBILITY IN WATER	% VOLATILE 72 – 75			OTHER			
Insoluble	VOC LBS./GAL 4.8-5.2			(IF ANY) None			
APPEARANCE							
AND ODOR Various colors, Honey	Like Subs	tance - Characteri	stic Odor				
SECTION IV-FIRE AND EXPLOSION							
FLASH POINT -10.0°F		FLAMMABLE LIMITS			UEL		
(METHOD USED) TCC			0.9		11.5		
EXTINGUISHING							
MEDIA Carbon Dioxide, Dry	Chemical	, or Foam					
SDECTAL FIDE							
FIGHTING PROCEDURES Self con	tained brea	thing apparatus w	ith a full face piece, operated	in pressure demand	or other positive	oressure mode.	
UNUSUAL FIRE AND							
EXPLOSION HAZARDS This materi	al is flamn	nable and may be i	gnited by heat, sparks, flame of	or static electricity.			
HAZARDOUS PRODUCTS FORMED	BY						
FIRE OR THERMAL DECOMPOSIT	ION C	arbon Dioxide and	or Carbon Monoxide				
EXPLOSIVE LIMITS							
(% BY VOLUME IN AIR) 0.9 – 11.5	<u> </u>						
SECTION V - OPTIONAL HAZARD	RATINGS	IDENTIFICAT					
HAZARD RATING	-		National Fire Protectio	n Association (NFP	'A)		
4-EXTREME		many ^					
3-HIGH	FIRE 3 REACTIV	11 YU					
2-MODERATE							
1-SLIGHT			DEALTH 2 CDE	HEALTH 2 SPECIAL HAZARDS None.			
0-INSIGNIFICANT			TEALIH STE	HEADIR 2 SIECIAL MARKADO MORCA			
**SEE SECTION IV							

This is the "front" when printed in duplex. Page 1 of 2 pages if not duplex.



CECONONIA STATE	SECTION VI - REACTIVITY AND STABILITY DATA						
	UNSTAB						
		s to Avoid) Strong acids, bases, oxi			with aikali metals and halogens.		
	DMPOSIT	ION OR BY PRODUCTS Carbon M			XIOYN		
HAZARDOUS	_	MAY OCCUR		ONDITIONS TO A			
POLYMERIZATION		WILL NOT OCCUR X	l M	lay be ignited by hea	at, sparks, flame or static electricity.		
SECTION VII - HEA	LTH HAZ						
ROUTES OF ENTRY	Y	INHALATION? YES SKI	IN? YES	INGESTION?	YES EYES? YES		
	UTE	X					
HAZARDS CH	IRONIC	X					
CARCINOGENICIT	Y: No						
SIGNS AND	_			<u> </u>			
SYMPTOMS OF	_	Headache, Dizziness, Drowsiness, Fa	atigue, Irre	egular Heartbeat, Ski	in and Eye Irritation.		
EXPOSURE							
MEDICAL CONDITI	IONS GE	NERALLY AGGRAVATED BY EX	XPOSURE	<u> </u>			
EMERGENCY AND	,	Ingestion: Contact Physician or Pois					
FIRST AID	_	Inhalation: Remove to fresh air. Ad	dminister O	en or Artificial l	Respiration if Necessary.		
PROCEDURES	•	Eye Contact: Flush with large amou	unts of wate	er. If irritation persi	sts, contact Physician.		
		Skin: Wash with soap and water.					
SECTION VIII - PRE	ECAUTIO	NS FOR SAFE HANDLING AND U	USE				
STEPS TO BE TAKE	EN .	Wipe up with floor absorbent. Trans	sfer to hoo	d. Prevent run-off to	o sewers,		
IN CASE MATERIA				maintain exposure below PEL's. Use sand or other material to dam or contain			
RELEASED OR SPII		spills. If large spill, notify appropria					
TODESTOLD STREET		3 1					
WASTE DISPOSAL	METHOL	S Dispose of product in accordance v	with local.	county, state and fe	deral regulations.		
PRECAUTIONS TO	BE	Avoid eve contact with eves. Keep of	container o	closed. Use with add	equate ventilation. Keep away from sparks, flame and heat		
TAKEN IN HANDLING sources and store in a cool area. Avoid inhalation of vapor					ersonal contact with liquid product.		
AND STORAGE		Use good personal hygiene practices					
ANDSTORIGE		200 800 0000000000000000000000000000000		0.14.00			
OTHER Keep Container Closed When Not In Use. Containers should be disposed of in an environmentally safe manner in accordance							
PRECAUTIONS Keep Container Closed When Not In Use. Containers should be disposed of in an environmentally sate manner in accordance with Governmental Regulations.							
SECTION IX - CONTROL MEASURES							
			the Airborn	o concentration	PROTECTIVE GLOVES		
RESPIRATORY PROTECTION (SPECIFY TYPE) Depending on the Airborne concentration use a Respirator with appropriate NIOSH approved cartridge or supplied air equipment.					Impervious Gloves		
			pinont,	SPECIAL None			
VENTILATION LOCAL EXHAUST Supplemental (if needed)					OTHER None		
MECHANICAL (GENERAL) To maintain exposure below PEL's					OTHER PROTECTIVE CLOTHING OR EQUIPMENT		
EYE PROTECTION Chaminal angular or approved eve protection					Chemcial Apron/Eye bath/Safety Shower		
Shermen spiton 8-86-45, or approved to the same of the							
WORK HYGIENIC PRACTICES Wash thoroughly after handling.							
SECTION X - TRANSPORTATION INFORMATION							
DOT PROPER SHIPPING NAME Coating Solution			DOT HAZARD CLASS 3				
DOT UN NUMBER UN 1139				DOT PACKING GROUP II			
IATA PROPER SHIPPING NAME Coating Solution				IATA HAZARD CLASS 3			
IATA UN NUMBER UN 1139				IATA PACKING	GROUP II		
SECTION XI - 313 SUPPLIER NOTIFICATION							
THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE							
EMERGENCY PLANNING AND COMMUNITY RIGHT -TO-KNOW ACT OF 1986, 40 CFR 372, (see table on page 1 for CAS # and percent by weight).							
Hexane, Toluene, and	l Methyl Etl	nyl Ketone					
WARNING: THIS P	PRODUCT	CONTAINS A CHEMICAL KNO	WN TO T	THE STATE OF CA	ALIFORNIA TO CAUSE CANCER AND BIRTH		
DEFECTS, OR OTHER REPRODUCTIVE HARM.							

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By:	Michael N Hindin	