

## DIVISION 6 WOOD, PLASTIC & COMPOSITE

### 06 10 00 Rough Carpentry

#### PART 1: GENERAL

##### 1.01 Scope of Standard

- A. This standard provides general guidance concerning the specific preferences of Texas State University for wood foundations; framing, sheathing, and decking using timber, lumber, and engineered wood products. Blocking and supports to join members and anchor framework to other construction.
- B. Texas State University recognizes that project conditions and requirements vary, thus precluding the absolute adherence to the items identified herein in all cases. However, unless there is adequate written justification, it is expected that these guidelines will govern the design and specifications for Texas State University projects.

##### 1.02 Quality Control

- A. All older campus building should be thoroughly checked for termites and other insect infestations, and specifications should address treatment measures required if termites are found during renovation.

#### PART 2: PRODUCTS

##### 2.01 General

- A. Contractor shall provide UL label for fire retardant material.
- B. Contractor shall provide certification for preservative treated material.
- C. Lumber shall be kiln dried, bearing stamp of Southern Pine Inspection Bureau or equivalent agency.
- D. Fire retardant treated lumber shall bear UL label.
- E. All treated lumber and plywood shall be Kiln Dried After Treatment (KDAT) 19%.
- F. Contractor shall install 2x10 wood blocking in walls for door wall stops.
- G. Contractor shall install treated lumber at exterior locations, where in contact with concrete, masonry, roofing or where subject to moisture.
- H. Contractor to use stainless steel fasteners for attachment of treated lumber or plywood.

#### PART 3: EXECUTION (NOT USED)

END OF SECTION 06 10 00